

# DHI-LDH55-SAI400K

Dahua 55 inch Wall-mounted LCD Digital Signage



#### Series Overview

Simple and elegant, the LCD Digital Signage is built of metal and has an industrial-grade design. With its A-level LCD panel, it has a long lifespan and displays high quality visuals. It can access the network, support audio and videos, release multimedia information, and broadcast advertisements.

#### Functions

#### **Rich Media**

A wide variety of media can be inserted into your projects such as images, videos, audio and files in Word, Excel, PPT, TXT or PDF format. It also supports insertion of webpages, streaming media, scrolling subtitles, notifications and more.

#### **Program Plug-ins**

Multiple elements can be incorporated into your projects, such as the weather, time and countdown timer, to suit your needs.

#### Local Release

Media can be conveniently imported to the digital signage through a USB flash drive to create and release projects.

#### **Release through the Network**

Projects can be easily created on the Media Publishing System (MPS) platform when the device is connected to the network, and then directly sent to the terminal device to be played.

#### **Play Plans**

The system simplifies broadcasting with general and cut-in plans. General plans, once activated, control how media is played on terminal devices. Cut-in plans can be directly released without approval.

- Designed with an industrial-grade panel. It works up to 16 hours a day.
- Includes a mainstream quad-core CPU, Android system, and decodes up to 4K resolution.
- Plays and releases programs in multiple modes.
- With intelligent split screen, its page layout can be freely adjusted, making it suitable for a variety of scenes.
- Designed with B/S architecture, the device manages programs by time and location, and generates operation reports.
- Supports encrypting platform data transmission, multi-level permission review for program release and terminal password protection.
- The device offers unified platform management, and can be remotely controlled by the platform.

#### **Play Modes**

The two play modes, carousel and temporary plan, add variety to the presentation of your projects. Carousel mode plays multiple media in a loop, with no need for manual configuration. Temporary plan mode fills in to play your media when there are no general plans and cut-in plans. It can be played with scrolling subtitles.

#### **Custom Play Time**

The play schedules are highly flexible. General plans can be scheduled to play weekly or you can personalize your own time schedule for them. Cut-in plans can be tailored by period, duration, and the number of play times.

#### **Scrolling Subtitles**

Subtitles can be set to scroll smoothly across the screen, displaying your desired content.

#### **Split Screen**

The screen can be divided into multiple windows, with each one showcasing different content.

#### **Remote Management**

From the comfort of the platorm, you can remotely power on and off the device, restart it, turn its display on and off, rotate its screen, and adjust its brightness and volume.

#### Scene

Ideal for communities, malls, supermarkets, hotels, enterprises, the government and various industries such as the advertising, catering, entertainment, tourism, culture, sports, education, finance, and healthcare industries.

## SAI Series | DHI-LDH55-SAI400K

Technical Specification		Gener	
LCD Panel		Power Si	
Panel Dimensions	55 inch	Power C	
Backlight	DLED	Standby	
LCD Technology	IPS/VA	Consum	
Aspect Ratio	16:9	Operatir	
Brightness	500 cd/m² (typ.)	Storage	
Contrast	IPS 1200:1(typ.) / VA 4000:1(typ.)	Operatn	
Display Colors	10 bit (8 bit + FRC), 1.07B colors	Storage	
Resolution	3840 (H) × 2160 (V)	Product	
Viewing Angle	178° (H); 178° (V)	Casing C	
Response Time	8 ms (typ.)	Product	
Surface Treatment	Haze 1%	Packagir	
Built-in System			
Operating System	Android 11.0	Net Wei	
CPU	4 cores A55, 1.92 GHZ	Gross W	
RAM	4 GB	Installati	
ROM	32 GB	Display I	
Video Decoding	H.265 HEVC MP-10@L5.1 up to 2160p@60 fps H.264 AVC HP@L5.1 up to 2160p@30 fps VP9 Profile 2 up to 2160p@60 fps H.264 MVC up to 1080p@60 fps MPEG-4 ASP@L5 up to 1080p@60 fps (ISO-13818) WMV/VC-1 SP/MP/AP up to 1080p@60 fps	Wall Mo Accesso Certif	
Function		Certifica	
Audio Compression	MPEG-3, WMA, WAV		
Video Compression	MPEG-4, H.264 AVC/MVC, H.265 HEVC	Order	
Video Format	mp4, avi, mov, mkv, wmv	Туре	
Device Ports		LCD Digi	
Network Port	1 × RJ–45 10/100/1000 Mbps self-adaptive Ethernet port	Dime	
Wi-Fi	Optional (External Wi-Fi module)		
Bluetooth	NO		
Data Transmission Ports	1 × USB 2.0 ports (type A) 1 × USB 3.0 ports (type A) 1 × TF card slot, up to 128 GB		
Video Input	1 × HDMI 2.1 (4K @60Hz)	1 1000 1000 1000 1000 1000 1000 1000 1	
Video Output	NO		
Audio Port	1 × 3.5 mm jack output	<u>I</u>	
IR Receiver	Yes		
Speaker			


General	
Power Supply	100–240 VAC, 50/60 Hz
Power Consumption	≤150 W
Standby Power Consumpton	≤ 0.5 W
Operating Temperature	0 °C to +40 °C (+32 °F to +104 °F) (avoid direct sunlight)
Storage Temperature	-20 °C to +60 °C (-4 °F to +140 °F)
Operatng Humidity	10%–85% (RH), non-condensing
Storage Humidity	10%–90% (RH), non-condensing
Product Material	Metal casing
Casing Color (Frame/Rear)	Black
Product Dimensions	1222.5 mm × 694.8 mm × 57.9 mm (48.13" × 27.35" × 2.28") (without bracket)
Packaging Dimensions	1357 mm × 150 mm × 853 mm (53.43" × 5.91" × 33.58")
Net Weight	15.5 kg (34.17 lb)
Gross Weight	22 kg (48.50 lb)
Installation	Wall mount
Display Mode	Landscape/Portrait
Wall Mount VESA	400× 400mm
Accessory	Wall-mount bracket, power cord, legal and regulatory information, energy label, user's manual, remote control
Certification	
Certifications	CE; ERP
Out of a state of a substate of	

#### Ordering Information

Туре	Model	Description
LCD Digital Signage	DHI-LDH55-SAI400K	Dahua 55 inch Wall-mounted LCD Digital Signage

### Dimensions (mm[inch])

• • • • • • • • • • •



. .

Rev 002.000 © 2024 Dahua. All rights reserved. Design and specificatons are subject to change without notce. Pictures in the document are for reference only, and the actual product shall prevail.

2 × 5 W

Built-in Speaker