MAXHUB

V6 Classic Series

The Classic series is MAXHUB's most popular Interactive Flat Panel for meetings, collaboration and presentations for our corporate partners. Fulfilling the need for a device which can host remote meetings and local discussions for all sizes of organization from start-up teams to multinational companies.

MAXHUB V6 Classic Series of IFP brings together all the functions a meeting room needs, such as wirelessscreen

sharing, whiteboarding, presenting as well as video conferencing with a high-quality camera and a wide microphone range. Every meeting room should have a MAXHUB V6 Classic series to enhance teamwork and increase organizational efficiency.







Professional 4K Display

High Color Accuracy, ∆E≤2 Wide Color Gamut, NTSC 90%

Touch Screen

20 Touch Points, Minimum Object Recognition - 2mm

Wireless Screen Sharing

Share your screen through MAXHUB Share app or wireless dongle

Smart Whiteboard

OCR supported, Multiple built -in templates



Built-in Camera

48million pixels Offer the best view in both dark/bright scene with WDR technology

10th Gen Intel CPU

Powerful performance, fluid experience * With use of MAXHUB PC Module

Ļ

Built-in Microphone

8 meters of voice pick-up8 mics arrays, clear conversations

Built-in Speaker

2.1 Channel 2x 10W + 20W

Classic Series

Display				
Model / Part No.	C5530	C6530	C7530	C8630
Diagonal Size (inch)	55	65	75	86
Backlight	Direct-lit LED	Direct-lit LED	Direct-lit LED	Direct-lit LED
Panel Technology	IPS	IPS	VA	VA
Aspect Ratio	16:9	16:9	16:9	16:9
Resolution	3840 x 2160	3840 x 2160	3840 x 2160	3840 x 2160
Refresh Rate	60Hz	60Hz	60Hz	60Hz
Response Time	8ms	8ms	8.5ms	8ms
Brightness (typ)	350cd/m ²	350cd/m ²	350cd/m ²	350cd/m ²
Contrast Ratio	1200:1	1200:1	5000:1	4000:1
Viewing Angle	178°/178°	178°/178°	178°/178°	178°/178°
Color Gamut (typ)	90% NTSC	90% NTSC	90% NTSC	90% NTSC
Display Orientation	Landscape	Landscape	Landscape	Landscape
Operating Hour	16/7	16/7	16/7	16/7
Dimension&Weight				
Product Dimensions	1263 x 776 x 88 mm	1488 x 903 x 88 mm	1709 x 1026 x 87 mm	1957.1 x 1160.1 x 100.2 mm
(WxHxD)	49.72 x 30.55 x 3.46 inch	58.58 x 35.55 x 3.46 inch	73.35 x 44.88 x 8.86 inch	77.05 x 45.67 x 3.94 inch
Shipping Dimensions (WxHxD)	1392 x 847 x 220mm 54.8 x 33.35 x 8.66 inch	1638 x 1005 x 208mm 64.09 x 39.57 x 8.19 inch	1863 x 1140 x 225 mm 73.35 x 44.88 x 8.86 inch	2110 x 1283 x 225 mm 83.07 x 50.51 x 6.86 inch
Net Weight (kg /pounds)	26.25kg / 57.87 lbs	36.25kg / 79.92 lbs	48.3kg / 106.48 lbs	59.75kg / 131.73 lbs
Gross Weight (kg /pounds)	34.2kg / 75.40 lbs	46.75kg / 103.07 lbs	62.8kg / 138.45 lbs	77.00kg / 169.76 lbs
Wall Mount (VESA)	400 x 200mm / 15.75 x 7.78inch	600 x 400mm / 23.62 x 15.75inch	800 x 400mm / 31.50x15.75inch	800 x 600mm / 31.50 x 23.62inch
Screws For VESA	M8 x 25mm / M8 x 0.99inch	M8 x 25mm / M8 x 0.99inch	M8 x 25mm / M8 x 0.99inch	M8 x 25mm / M8 x 0.99inch

02

Power Supply	AC100-240V,50/60Hz	AC100-240V,5	0/60Hz	AC100-240V,50/60Hz	AC100-240V,50/60Hz		
Max Power Consumption	300W	350W		400W	400W		
Standby	≪0.5W	≪0.5W		≪0.5W	≪0.5W		
Touch System			Connectivity				
Touch Sensor	IR Touch		Input	HDMI IN x 1 , USB 2.0 x 1,	USB 3.0 x 2, TOUCH 2.0 x 1 , USB Type-C x 2		
Max Touch Points Supported	20		Audio		Audio out x 1		
Accuracy	±1mm		Control	RS232 x 1			
Object Recognition Range	≥2mm		PC Module Slot	Yes, 3840 x 2160@60fps			
Glass	Zero parallax , 3mm Angi-glare, Antibacterial		PC Module	Module MAXHUB PC Module			
Supported Operating	Windows10/Windows8/Windows7/WindowsXP/ Android/Linux/Mac OS X/Chrome OS		Wifi Module		SI06		
System (Touch Return)							
Camera/Audio/Microphone			Environmen	Environment			
Built-in Camera	Yes, Single Camera, 48	MP	Operating Temp	erature	0 °C ~40 °C		

Camera Features

Auto Frame / Speaker Tracking

Storage Temperature 10%~90%RH

