



1. MATERIALS

- 1.1 CABLE: {[(28AWG TC*1C+SP(28AWG CCS)]*3COAX+28AWG CCS*7C} +AM+D+B(64/0.12ALM)+ BLACK PVC JACKET; OD: 8. 2 ± 0 . 2mm.
- CABLE MARKING: Inline LOW VOLTAGE COMPUTER CABLE 80°C 30V
- 1.2 P1&P2: HDB 15PIN MALE: BLACK PBT INSULATION, EMPTY NINE PIN, GOLD FLASH CONTACTS, NICKEL PLATED SHELL;
- 1.3 HOOD MOLDED BLACK PVC.
- 1.4 THUMB SCREW TO BE MOLDED BLACK PVC.
- 1.5 FERRITE (φ17.5*φ9.5*28.5MM) TO BE MOLDED BLACK PVC. 2 100% OPEN AND SHORT TEST.
- 3. PACKING: 1PCS/POLYBAG.
- 4. ALL MATERIAL BE ROHS COMPLIANT.





Art. Nr.	Länge	EAN
17803B	0,3 m	4043718090198
17805B	0,5 m	4043718090204
17702B	1 m	4043718090211
17715B	1,5 m	4043718090228
17719B	2 m	4043718016358
17710B	3 m	4043718076345
17718B	5 m	4043718084180
17723B	7 m	4043718086832
17717B	10 m	4043718058082
17713B	15 m	4043718076338

S-VGA Kabel Stecker/Stecker schwarz mit doppelt abgeschirmten Leitungen, für eine optimale Bildqualität. Komplett belegtes Kabel (ohne Pin 9).

- S-VGA Kabel, schwarz
- 15pol HD Stecker an 15pol HD Stecker
- schwarze Stecker, vergossen
- doppelte Folien-Abschirmung plus Geflecht
- volle Pin-Belegung, 3 Koaxial- plus 7 Steuerleitungen (Pin 9 nicht belegt)

