Panasonic

Wireless presentation system **USB-C** Transmitter

TY-WP2BC1 **TY-WPBC1**



Set content

Number	TY-WP2BC1	TY-WPBC1
Set content	Transmitter x 2 , Case for Transmitter	Transmitter x 1
Carton dimensions	W250 x H89 x D180 mm (W9.85" x H3.51" x D7.09")	W155 x H62 x D105 mm (W6.11" x H2.45" x D4.14")
Gross weight	1.2 kg / 2.64 lbs	345 g / 0.77 lb
Accessories	Conversion adaptor for pairing, Opretaing manual	

Transmitter

PRODUCT SPECIFICATION


(design and specification subject to change without notice)		
1920 x 1080/60p (USB-C IN)		
Max.433 Mbps		
5 GHz band 5,150 MHz - 5,250 MHz 36 40 44 48 Channel		
IEEE802.11ac		
Yes		
(Main button) Red: Trying to connect White: Connecting Green: Display Blue: Fixed mode (Sub button) Green: Multi connection		
30 m (When the line of sight/wave conditions are good)		
USB-C (female)/USB-A (male)		
DC 5 V/0.9 A		
4.5 W		
W51 x H26 x D73 mm [W2.00" x H"1.00 x D2.86"]		
W51 x H26 x D178mm [W2.00" x H"1.00 x D6.98"]		
approx.110 g/ 0.3 lbs		
Black		
Plastic		
Yes		
Temperature: 0 $^{\circ}$ C to 35 $^{\circ}$ C (32 $^{\circ}$ F to 95 $^{\circ}$ F) Humidity: 20% to 80% (No condensation)		
Temperature: -20 °C to 60 °C (-4 °F to 140 °F)		
Humidity: 20% to 80% (No condensation)		
CE, FCC, MIC		

UIST OF CORRESPONDENCE SIGNALS


USB-C input signal type		
1920x1080@60Hz	1280x720@60Hz	
1920x1080@50Hz	1280x720@50Hz	
1920x1080@30Hz		

DIMENSIONS

Units: mm [inch]



O CONNECTION TERMINAL



Units: mm [inch]

Case for Transmitter

PRODUCT SPECIFICATION

(design and specification subject to change without notice)

SPECIFICATION		
W151.3 x H41.6 x D198.0 mm (6.0" x 1.7" x 7.8)		
approx.315 g/ 0.7 lbs		
Black		
Plastic		
ENVIRONMENTAL		
Temperature: -20 °C to 60 °C (-4 °F to 140 °F) Humidity: 20% to 80% (No condensation)		

