Hisense

75" Advanced Interactive Display





75WR6CE 75" ADVANCED INTERACTIVE DISPLAY

Our WR series of Hisense Interactive Digital Display include the latest smart features to improve collaboration and create a leading engaging experience for users. The new WR series is available in 3 sizes (65", 75", 86") and their 4K Ultra HD picture quality ensures perfect colour and rich detail. They are touch enabled allowing multiple people to use them at once to present, illustrate and share information. When using the digital whiteboard, our improved IR software now recognises touch points as little as 2mm ensuring the experience is as accurate as writing with pen and paper. New for 2022, the WR range features an optical bonded display that diffuses reflections and bright light to keep the display visible in any lighting conditions. Users can also now wirelessly connect with two or more additional Hisense displays.

Highlights



4K Ultra HD

The 4K Ultra HD picture quality ensures perfect colour and rich details in all possible surroundings. In addition to the 4K screen as always, we bring 4K UI for WR6CE. With 4K UI, we can make the most of this clear, bright, eye-protective screen for a more beautiful display.



Anti-Glare

Optical technology diffuses mirror-like reflections and bright lights to help keep what's on your screen clear and visible.



Comfortable viewing

Low blue light and full frequency DC dimming from hardware, bring the ultimate comfort viewing experience.



Settings menu lock

Now you can set a separate password lock for the settings menu to prevent children from accidentally touching it.



Screen transmission

The WR6CE interactive digital board can wirelessly connect with two or more auxiliary screen devices. Near-Field Communication (NFC) touch transmission and A&C screen transmission simplify this process.



Wide viewing angle

The extra wide 178° viewing angle is a perfect fit for classrooms and presentations, with perfect colour and rich details in all possible surroundings.



Collaborative interaction

The touchscreen recognizes up to 20 touches at once which is ideal for simultaneous use by meeting participants.



Newly upgraded whiteboard

Add sticky note function to jot down your thoughts. You can view all the pages through the page list, adjust the page order, and copy content across pages.







Hisense

Interactive Display Panel

| LCD Size | 75″ |
|----------------------|-------------------|
| Backlight Type | D-LED |
| Resolution | 3840x2160(pixels) |
| Brightness | 350cd/m²(typ.) |
| Contrast Ratio | 1200:1(typ.) |
| Response Time | 8ms (typ.) |
| Refreshing Frequency | 60Hz |
| Viewing Angle | 178°(H) / 178°(V) |
| Lifetime | 50,000 hrs (min.) |
| Color Gamut(X% NTSC) | 72% |
| Display Colors | 1.07B(10bit) |

System


| OS | Android 8.0 |
|----------|--|
| Language | Chinese, English, Polish, German, French, Italian, Spanish, Finnish, Norwegian, Swedish, Thai, Indonesian, Japanese |
| | |

Speaker

| Audio Output Power | 2x15W |
|--------------------|---|
| Connectivity | |
| WI-FI | IEEE 802.11a/b/g/n/ac/ax(2.4G and 5G) IEEE 802.11a/b/g/n/ac(2.4G and 5G) |
| Bluetooth | BT5.1 |
| Input | HDMI(2.0) IN x 2 DP(1.2a) IN x 1 OPS(optional) x 1 LAN x 1 USB2.0 x 1 USB3.0 x 2 Type-C x 1 Touch x 1 RS232 IN x 1 Service x 1 |
| Output | HDMI OUT x 1 S/PDIF OUT x 1 Audio OUT x 1 |
| Touch | |
| Sensing Type | Infrared Touch Frame |
| Surface Protection | Anti-Glare Glass |
| | |

| Surface Protection | Anti-Glare Glass |
|------------------------|------------------|
| Infrared Touch | ≤20 points |
| Touch Accuracy | 90%(±1mm) |
| Theory Clicks | Unlimited |
| Minimum Touch Object | ≥2mm |
| Windows 10/8/7,Android | Multi Touch |

| Power | |
|-------------------------------|------------------------------|
| Denne De en incerente | |
| Power Requirements | AC 100 V ~ 240 V, 50/60 Hz |
| Power Consumption Without OPS | 260W |
| Standby Consumption | <0.5W |
| Physical | |
| Housing Color | Black |
| Product Size (W x H x D) | 1710 × 1022 × 103mm |
| Package Size (W x H x D) | 1896 × 300 × 1184mm |
| Net Weight | 45.8kg |
| Packed Weight | 59.6kg |
| VESA | 600x600mm, 4-M8 screw |
| Optional | |
| | Mobile Cart |
| Basic | OPS |
| What's in the box | |
| | User Manual × 1 |
| | Pen × 2 |
| | Remote Control × 1 |
| Basic | Wireless Cast × 1 (Optional) |
| | Power Cable × 1 |
| | Battery × 2 |
| | Wall Mount Bracket × 1 |
| Dimensions | |
| 1710 1077 107 | |



HISENSE B2B EUROPE Beechavenue 139, 1119 RB Schiphol-Rijk, Netherlands

www.hisense-b2b.com sales@hisense-b2b.com