

DHI-LDH43-WAI200L

Dahua 43 inch LCD Digital Signage



Series Overview

Simple and elegant, the LCD Digital Signage is built of metal and has an industrial-grade design. With its A-level LCD panel, it has a long lifespan and displays high quality visuals. It can access the network, support audio and videos, release multimedia information, and broadcast advertisements.

Functions

Rich Media

A wide variety of media can be inserted into your projects such as images, videos, audio and files in Word, Excel, PPT, TXT or PDF format. It also supports insertion of webpages, streaming media, scrolling subtitles, notifications and more.

Program Plug-ins

Multiple elements can be incorporated into your projects, such as the weather, time and countdown timer, to suit your needs.

Local Release

Media can be conveniently imported to the digital signage through a USB flash drive to create and release projects.

Release through the Network

Projects can be easily created on the Media Publishing System (MPS) platform when the device is connected to the network, and then directly sent to the terminal device to be played.

Play Plans

The system simplifies broadcasting with general and cut-in plans. General plans, once activated, control how media is played on terminal devices. Cut-in plans can be directly released without approval.

- Designed with an industrial-grade panel. It works up to 24 hours a day.
- Includes a mainstream quad-core CPU and Android system.
- Plays and releases programs in multiple modes.
- With intelligent split screen, its page layout can be freely adjusted, making it suitable for a variety of scenes.
- Designed with B/S architecture, the device manages programs by time and location, and generates operation reports.
- Supports encrypting platform data transmission, multi-level permission review for program release and terminal password protection.
- The device offers unified platform management, and can be remotely controlled by the platform.

Play Modes

The two play modes, carousel and temporary plan, add variety to the presentation of your projects. Carousel mode plays multiple media in a loop, with no need for manual configuration. Temporary plan mode fills in to play your media when there are no general plans and cut-in plans. It can be played with scrolling subtitles.

Custom Play Time

The play schedules are highly flexible. General plans can be scheduled to play weekly or you can personalize your own time schedule for them. Cut-in plans can be tailored by period, duration, and the number of play times.

Scrolling Subtitles

Subtitles can be set to scroll smoothly across the screen, displaying vour desired content.

Split Screen

The screen can be divided into multiple windows, with each one showcasing different content.

Remote Management

From the comfort of the platform, you can remotely power on and off the device, restart it, turn its display on and off, rotate its screen, and adjust its brightness and volume.

Scene

Ideal for communities, malls, supermarkets, hotels, enterprises, the government and various industries such as the advertising, catering, entertainment, tourism, culture, sports, education, finance, and healthcare industries.

Technical Specification	
LCD Panel	
Panel Dimensions	43 inch
Backlight	DLED
LCD Technology	IPS
Aspect Ratio	9: 16
Brightness	3000 cd/m² (typ.)
Contrast	1200: 1 (typ.)
Display Colors	8 bit, 16.7M colors
Resolution	1080 (H) × 1920 (V)
Viewing Angle	178° (H); 178° (V)
Response Time	8 ms (typ.)
Surface Treatment	Haze 25%
Built-in System	
Operating System	Android 11.0
CPU	4 cores A55, 1.92 GHZ
RAM	4 GB
ROM	32 GB
Video Decoding	H.265 HEVC MP-10@L5.1 up to 2160p@60 fps H.264 AVC HP@L5.1 up to 2160p@30 fps VP9 Profile 2 up to 2160p@60 fps H.264 MVC up to 1080p@60 fps MPEG-4 ASP@L5 up to 1080p@60 fps (ISO-13818) WMV/VC-1 SP/MP/AP up to 1080p@60 fps
Function	
Audio Compression	MPEG-3, WMA, WAV
Video Compression	MPEG-4, H.264 AVC/MVC, H.265 HEVC
Video Format	mp4, avi, mov, mkv, wmv
Device Ports	
Network Port	$1 \times RJ-45$ 10/100/1000 Mbps self-adaptive Ethernet port
Wi-Fi	Optional (External Wi-Fi module)
Bluetooth	NO
Data Transmission Ports	1 × USB 2.0 ports (type A) 1 × USB 3.0 ports (type A) 1 × TF card slot, up to 128 GB
Video Input	1 × HDMI 2.1 (1080P @60Hz)
Video Output	NO
Audio Port	1 × 3.5 mm jack output
IR Receiver	Yes
Speaker	
Built-in Speaker	2 × 5 W


Power Supply	180-264V, 50/60Hz
Power Consumption	≤270 W
Standby Power Consumption	≤15 W with fans
Operating Temperature	0 °C to +40 °C (+32 °F to +104 °F)
Storage Temperature	-10 °C to +60 °C (14 °F to +140 °F)
Operating Humidity	10%–85% (RH), non-condensing
Storage Humidity	10%-90% (RH)
Product Material	Metal casing
Casing Color (Frame/Rear)	Black
Product Dimensions	568 mm x 980 mm x 85.3 mm
Packaging Dimensions	1130 mm x 236 mm x 833 mm
Net Weight	32kg
Gross Weight	40kg
Installation	Ceiling mount/Wall mount
Display Mode	Portrait
Wall Mount VESA	400 mm × 300mm
Accessory	Ceiling mount bracket, power cord, legal and regulatory information, remote control, screw

Certification


Certifications	CE, ERP

Ordering Information Type Model Description LCD Digital Signage DHI-LDH43-WAI200L Dahua 43 inch LCD Digital Signage

Dimensions (mm[inch])







Rev 002.000

2023 Dahua. All rights reserved. Design and specifications are subject to change without notice.